

SPR 250



ajpmotos.com

MOTEUR

TYPE

Mono-cylindre, 4 temps, 4 soupapes - DOHC - refroid. eau

DIAM. X COURSE

77 x 53.6mm

CYLINDRÉE

249cc

DÉMARRAGE

Électrique

SYSTEME CARBURANT

Injection Athena GET Ø34mm

TRANSMISSION

6 vitesses

EMBRAYAGE

Humique, multi-disques

ENGINE

TYPE

Single cylinder , 4 stroke, 4 valves - SOHC - liquid cooled

BORE X STROKE

77 x 53.6mm

DISPLACEMENT

249cc

STARTER

Electric

FUEL SYSTEM

Athena GET fuel injection system Ø34mm

TRANSMISSION

6 speed

CLUTCH

Oil bath, multi-disc

SPÉCIFICATIONS & DIMENSIONS

CADRE

Tri-porteur aluminium-acier

EMPATTEMENT

1450mm

HAUTEUR DE SELLE

930mm *Enduro*

910mm *Supermotard*

GARDE AU SOL

355mm *Enduro*

305mm *Supermotard*

RÉSERVOIR ESSENCE

9.5L

SPECS & DIMENSIONS

FRAME

Aluminium-steel composite

WHEELBASE

1450mm

SEAT HEIGHT

930mm *Enduro*

880mm *Supermoto*

GROUND CLEARANCE

355mm *Enduro*

305mm *Supermoto*

FUEL TANK

9.5L

ROUE, SUSPENSION & FREIN

PNEU AVANT

90/90 21" *Enduro*

100/80 17" *Supermotard*

PNEU ARRIERE

120/90 18" *Enduro*

130/70 17" *Supermotard*

SUSPENSION AVANT

ZF Sachs Ø48mm - 300mm débat, totalement réglable

SUSPENSION ARRIERE

ZF Sachs progressive avec bombonne

300mm débattement, totalement réglable

FREIN AVANT

Étrier BREMBO double piston

Disque Ø260mm

FREIN ARRIERE

Étrier BREMBO simple piston

Disque Ø220mm

WHEEL, SUSPENSION & BRAKES

FRONT TYRE

90/90 21" *Enduro*

100/80 17" *Supermoto*

REAR TYRE

120/90 18" *Enduro*

130/70 17" *Supermoto*

FRONT SUSPENSION

ZF Sachs Ø48mm - 300mm travel, fully adjustable

REAR SUSPENSION

ZF Sachs prog.system w/ reservoir

300mm travel, fully adjustable

FRONT BRAKE

BREMBO caliper, dual piston

Ø260mm disc

REAR BRAKE

BREMBO caliper, single piston

Ø220mm disc