

SPR SIOR



ajpmotos.com

MOTEUR

TYPE

Mono-cylindre, 4 temps, 4 soupapes - DOHC - refroid. eau

DIAM. X COURSE

97 x 67.5mm

CYLINDRÉE

501cc

DÉMARRAGE

Électrique

SYSTEME CARBURANT

Injection Athena GET Ø45mm

TRANSMISSION

6 vitesses

EMBAYAGE

Humique, multi-disques

ENGINE

TYPE

Single cylinder , 4 stroke, 4 valves - DOHC - liquid cooled

BORE X STROKE

97 x 67.5mm

DISPLACEMENT

501 cc

STARTER

Electric

FUEL SYSTEM

Athena GET fuel injection system Ø45mm

TRANSMISSION

6 speed

CLUTCH

Oil bath, multi-disc

SPÉCIFICATIONS & DIMENSIONS

CADRE

Tri-porteur aluminium-acier

EMPATTEMENT

1450mm

HAUTEUR DE SELLE

960mm *Enduro*

910mm *Supermotard*

GARDE AU SOL

355mm *Enduro*

305mm *Supermotard*

RÉSERVOIR ESSENCE

9.5L

SPECS & DIMENSIONS

FRAME

Aluminium-steel composite

WHEELBASE

1450mm

SEAT HEIGHT

960mm *Enduro*

910mm *Supermoto*

GROUND CLEARANCE

355mm *Enduro*

305mm *Supermoto*

FUEL TANK

9.5L

ROUE, SUSPENSION & FREIN

PNEU AVANT

90/90 21" *Enduro*

120/70 17" *Supermotard*

PNEU ARRIERE

140/80 18" *Enduro*

150/60 17" *Supermotard*

SUSPENSION AVANT

ZF Sachs Ø48mm Double cartouche fermée
300mm débattement, totalement réglable

SUSPENSION ARRIERE

ZF Sachs progressive avec bombonne
300mm débattement, totalement réglable

FREIN AVANT

Étrier BREMBO double piston
Disque Ø260mm

FREIN ARRIERE

Étrier BREMBO simple piston
Disque Ø220mm

WHEEL, SUSPENSION & BRAKES

FRONT TYRE

90/90 21" *Enduro*

120/70 17" *Supermoto*

REAR TYRE

140/80 18" *Enduro*

150/60 17" *Supermoto*

FRONT SUSPENSION

ZF Sachs Ø48mm Closed cartridge fork
300mm travel, fully adjustable

REAR SUSPENSION

ZF Sachs prog.system w/ reservoir
300mm travel, fully adjustable

FRONT BRAKE

BREMBO caliper, dual piston
Ø260mm disc

REAR BRAKE

BREMBO caliper, single piston
Ø220mm disc